


BSPT barrel nipple

Nom size	A	B BSPT	Max Op @ 150°C Pressure (bar)	Stock No
1/4"	30.0	1/4"	10	6096-5006
3/8"	40.0	3/8"	10	6096-5009
1/2"	60.0	1/2"	10	6096-5013
3/4"	60.0	3/4"	10	6096-5019
1"	60.0	1"	10	6096-5026
1 1/4"	80.0	1 1/4"	10	6096-5031
1 1/2"	80.0	1 1/2"	10	6096-5038
2"	100.0	2"	10	6096-5051
2 1/2"	100.0	2 1/2"	10	6096-5064
3"	120.0	3"	10	6096-5076



Technical Data:

- Material: 316 Stainless Steel
- Finish: Descaled
- Pressure/Temperature: See above
- Associated standards: BS BS1740, BS1387
- Applications : Non-hygienic
- Tolerance: +/- 0.5mm
- Seals: PTFE Tape

- We stock a comprehensive range of BSP fittings including unions, ferrules, bends, tees, reducers, hoseliners and adaptors
- Components can be fabricated to customer specification
- Fabrication capabilities include frameworks, skid mounted systems, manifolds, jacketed assemblies, adaptors, flowplates and spool pieces.
- In-house services include machining, welding, fabrication, polishing.

D6096 – V01

NOTES

FORM No:FM002-V02

Axium Process Ltd
Hendy Industrial Estate
Hendy, Swansea
SA4 0XP UK

- Dimensions are provided in good faith but maybe subject to change
- Seals must be chosen for required operating medium & temperature

(T) +44 (0)1792 883 882
 (F) +44 (0)1792 886 049
 (E) info@axiumprocess.com
 (W) www.axiumprocess.com