


Stainless steel sprayballs

To complement our range of tank manways, we supply static sprayballs, nozzles and rotating sprayheads as a cost effective solution for many tank washing duties.


- Manufactured in 316L stainless steel
- 180° upward, 180° downward and 360° spray patterns
- Customised spray patterns to order
- Screw in or clip on options available
- Fabricated sprayball assemblies to customer specification




180° upward



180° downward



360°



Dimensions				Normal operating pressure	Flowrates		Cleaning radius
Coverage	Supply tube OD	Ball diameter	Spray hole diameter	bar	Imperial gall/hr	m ³ /hr	Effective cleaning radius, m
360	¾"	1 ½"	1/16"	1.40	780	3.55	0.90
180D	¾"	1 ½"	1/16"	1.40	480	2.18	0.80
180U	¾"	1 ½"	1/16"	1.40	540	2.45	0.80
360	1"	2 ½"	3/32"	1.40	3,420	15.54	1.80
180D	1"	2 ½"	3/32"	1.40	2,040	9.27	1.80
180U	1"	2 ½"	3/32"	1.40	2,460	11.18	1.80
360	1 ½"	2 ½"	3/32"	1.40	3,420	15.54	1.80
180D	1 ½"	2 ½"	3/32"	1.40	2,040	9.27	1.80
180U	1 ½"	2 ½"	3/32"	1.40	2,640	12.00	1.80
360	1 ½"	3 ½"	3/32"	1.40	5,760	26.18	3.65
360	2"	3 ½"	3/32"	1.40	5,760	26.18	3.65
180U	2"	3 ½"	3/32"	1.40	3,420	15.54	3.65
180D	2"	3 ½"	3/32"	1.40	3,060	13.91	3.65
180S	1 ½"	2 ½"	3/32"	1.40	2,100	9.54	1.80
180S	1 ½"	2 ½"	3/32"	3.60	4,740	21.54	3.80
180S	1 ½"	3 ½"	3/32"	1.40	4,020	18.27	4.50
180S	1 ½"	3 ½"	3/32"	3.80	6,480	29.45	7.60

D = down

U = up

S = sideways

Axium Process Ltd

Hendy Industrial Estate, Hendy

Swansea, UK

SA4 0XP

Tel: +44 (0) 1792 883882

Fax: +44 (0) 1792 886049

Email: info@axiumprocess.com

Web: www.axiumprocess.com



All data is provided in good faith and is subject to change

Copyright 2003 Ref: MAN04-01