
DATA SHEET www.axiumprocess.com



1018

RJT pressed blank 316

Nom size	Α	В	Stock number
1"	41.0	8.0	1018-5026
1 1⁄2"	54.0	8.0	1018-5038
2"	67.0	9.0	1018-5051
2 1⁄2"	79.0	9.0	1018-5064
3"	92.0	9.0	1018-5076
4"	118.0	9.0	1018-5102



TECHNICAL DATA			
Associated Standards	BS 4825 : Part 5 : 1991 (1"-4" inclusive)		
Material	316 Stainless Steel		
Material Certification	BS EN 10204/DIN 50049 3.1		
Applications	RJT fittings are suitable for frequently dismantled section of pipework used widely in the food, beverage and dairy industries.		
RJT Fittings Range	Unions, blanks, tees, bends, hoseliners, adaptors, concentric & eccentric reducers, Y pieces		
Seals	EPDM, Nitrile, Silicone, Solid PTFE, Viton [®] (Viton is a registered trade mark of Dupont Dow Elastomers).		
Notes	Dimensions are provided in good faith. If dimension are critical please confirm before ordering		
	Seals must be chosen for required operating medium and temperature		
GENERAL CAPABILITIES			
	ion, Hygienic Process Plant, Project Management, In-house Manual and Orbital Welding, achining, Fabrication and Polishing, Component Customisation		
Full materials certification, weld maps, logs, welder qualifications and weld procedures, pickling, passivation and ferroxyl certification.			

D1018-V02 / ECN 733

CUSTOMISED STAINLESS STEEL SYSTEMS, FABRICATIONS AND COMPONENTS

Axium Process Ltd

Hendy Industrial Estate, Hendy, Swansea, UK SA4 0XP Tel: +44 (0) 1792 883882 +44 (0) 1792 886049 Fax: Email: info@axiumprocess.com Web: www.axiumprocess.com



All data is provided in good faith and is subject to change