


5281

ASME BPE Clamp ended concentric reducer 316L

Nom size		Dim	Stock number
А	В	L1	
3/4"	1⁄2"	50.8	5281-6019-013
1"	1/2"	63.5	5281-6026-013
1"	3/4"	50.8	5281-6026-019
1 1⁄2"	3/4"	76.2	5281-6038-019
1 1⁄2"	1"	76.2	5281-6038-026
2"	1"	127.0	5281-6051-026
2"	1 1⁄2"	76.2	5281-6051-038



TECHNICAL DATA		
Associated Standards	ASME BPE - 2009	
Material	316L Stainless Steel / LS 1.4435	
Material Certification	BS EN 10204/DIN 50049 3.1 for all wetted parts	
Finish	SF1 (0.5 µm, mechanical)	
Pressure/Temperature	Up to 10 bar at 20°C	
Tolerance	To ASME BPE tolerances	
Options	Sizes up to 6" available We also supply plain ended options which are ASME BPE compliant	
Clamp Fittings Range	Unions, ferrules, blanks, tees, bends, hoseliners, adaptors, concentric & eccentric reducers, Y pieces	
Seals	FDA & USP Class VI approved polymers including EPDM, Nitrile, Silicone, Platinum Cured Silicone, Encapsulated & Solid PTFE, Viton [®] (Viton is a registered trade mark of Dupont Dow Elastomers).	
Notes	Dimensions are provided in good faith. Seals must be chosen for required operating medium and temperature	
GENERAL CAPABILITIES		
	ation, Hygienic Process Plant, Project Management, In-house Manual and Orbital Welding, Machining, Fabrication and Polishing, Component Customisation	
Full materials certification, weld maps, logs, welder qualifications and weld procedures, pickling, passivation and ferroxyl certification.		

D5281-V01

CUSTOMISED STAINLESS STEEL SYSTEMS, FABRICATIONS AND COMPONENTS

Axium Process Ltd

Hendy Industrial Estate, Hendy, Swansea, UK SA4 0XP Tel: +44 (0) 1792 883882 +44 (0) 1792 886049 Fax: Email: info@axiumprocess.com Web: www.axiumprocess.com



All data is provided in good faith and is subject to change