


8073

Plain-ended hosetail 316L

Nom size	A	B	R	Stock No
1/2"	12.7	50	24	8073-6013
5/8"	19.1	50	24	8073-6016
3/4"	19.1	50	24	8073-6019
*1"	25.4	50	24	8073-6026
*1 1/2"	38.1	50	24	8073-6038
*2"	50.8	80	39	8073-6051
*2 1/2"	63.5	80	39	8073-6064
*3"	76.2	100	51	8073-6076
*4"	101.6	100	51	8073-6102



TECHNICAL DATA	
Associated Standards	*BS 4825 : Part 2 : 1991, ASTM A269, ASTM A270, ASTM A312
Material	316L Stainless Steel
Material Certification	BS EN 10204/DIN 50049 3.1 for all wetted parts
Finish	Welds ground ID & OD, Polished 0.8Ra (0.4 Ra available)
Tolerance	+/- 1.0mm
Plain-Ended Fittings Range	Tees, 90°, 45° & 180° bends, hosetails, concentric & eccentric reducers, Y pieces, Crosses
Seals	FDA & USP Class VI approved polymers including EPDM, Nitrile, Silicone, Platinum Cured Silicone, Encapsulated & Solid PTFE, Viton® (Viton is a registered trade mark of Dupont Dow Elastomers).
Notes	Dimensions are provided in good faith. Seals must be chosen for required operating medium and temperature
GENERAL CAPABILITIES	
Design and System Fabrication, Hygienic Process Plant, Project Management, In-house Manual and Orbital Welding, Machining, Fabrication and Polishing, Component Customisation	
Full materials certification, weld maps, logs, welder qualifications and weld procedures, pickling, passivation and ferroxyl certification.	

D8073-V02 / ECN 730

CUSTOMISED STAINLESS STEEL SYSTEMS, FABRICATIONS AND COMPONENTS

Axium Process Ltd

Hendy Industrial Estate, Hendy, Swansea, UK SA4 0XP

Tel: +44 (0) 1792 883882

Fax: +44 (0) 1792 886049

Email: info@axiumprocess.com

Web: www.axiumprocess.com



All data is provided in good faith and is subject to change