

HYGIENIC STAINLESS STEEL SPRAYBALLS



**316L STAINLESS
STEEL**

**360°, 180° UPWARD,
180° DOWNWARD
OPTIONS**

RETAINING 'D' CLIP

**1½" – 3½" BALL
DIAMETERS**

SELF-DRAINING

**CUSTOMISED
ASSEMBLIES**

**Axium Process Ltd
Hendy Industrial Estate
Hendy
Swansea SA4 0XP**

**Tel: 01792 883 882
info@axiumprocess.com
www.axiumprocess.com**



Our range of hygienic 316L stainless steel sprayballs are self draining and are capable of effectively distributing both water and cleaning solutions onto the internal surface area of tanks and vessels.

We specialise in customised sprayball assemblies and lances, and our engineers are on hand to offer advice on the best design for a given application as well as assist with flow rate calculations.

Dimensions				Applied Pressure	Flow rates		Cleaning Ø	Stock No
Coverage	Supply Tube OD	Ball Ø (mm)	Spray Hole Ø (mm)		Imperial gal/hr	m ³ /hr		
360	1"	65	1.6	2.0	1980	9	1.9	8143-6026
360	1.5"	65	1.6	2.0	2180	9.9	2.0	8143-6038
360	2"	89	1.6	2.0	3500	15.9	3.0	8146-6051
180U	1"	65	1.6	1.95	1320	6	1.20	8145-6026
180U	1.5"	65	1.6	2.0	1430	6.5	1.30	8145-6036
180D	1"	65	1.6	2.0	770	3.5	0.75	8144-6026
180D	1.5"	65	1.6	1.95	770	3.5	0.75	8144-6038